

Maintenance | Achieve

INITIAL MAINTENANCE

RECOMMENDED PRODUCTS: We recommend Diversy Profi, diluted to a degree of 10 oz. per gallon of water, used in conjunction with a microfiber mop or 3M's Red Buffer Pad 5100.

- 1. Remove all surface dirt and debris by vacuuming, sweeping, or wiping with damp cloth or microfiber mop (Rubbermaid Reveal Spray Mop recommended). We recommend commercial grade electric auto scrubber/extractor equipment for large or highly trafficked areas. If using commercial cleaner, use the softest bristle attachment available or red buffer pads with minimum pressure.
- 2. Scrub the area using approved cleaning solution (10 oz. per gallon of water) and low speed buffer or microfiber mop. Avoid flooding. Note: Flooding or excess water can lead to weakened or split seams. Cleaning solution should always be dispensed as a misted spray.
- 3. Pick up solution with a wet vacuum.
- 4. Rinse with clean water misted onto floor and remove with wet vacuum or floor extractor.
- 5. Repeat rinsing (step 4) until removed water is clean.
- 6. Allow floor to dry thoroughly before use (6 8 hrs).

REGULAR MAINTENANCE

RECOMMENDED PRODUCTS: We recommend Diversy Profi, diluted to a degree of 2 - 4 oz. per gallon of water, used in conjunction with a microfiber mop or 3M's Red Buffer Pad 5100.

- 1. Remove all surface dirt and debris by vacuuming, sweeping, or wiping with damp cloth or microfiber mop (Rubbermaid Reveal Spray Mop recommended). We recommend commercial grade electric auto scrubber/extractor equipment for large or highly trafficked areas. If using commercial cleaner, use the softest bristle attachment available or red buffer pads with minimum pressure.
- 2. Scrub the area using approved cleaning solution (10 oz.

per gallon of water) and low speed buffer or microfiber mop. Avoid flooding. Note: Flooding or excess water can lead to weakened or split seams. Cleaning solution should always be dispensed as a misted spray.

3. Pick up solution with a wet vacuum if necessary.

RESTORATIVE CLEANING FOR HEAVILY SOILED FLOORING

RECOMMENDED PRODUCTS: We recommend Diversy Profi, diluted to a degree of 16 oz. per gallon of water, used in conjunction with a microfiber mop or 3M's Blue Cleaner Pad 5300.

- 1. Heavily scrub the area using approved cleaning solution (16 oz. per gallon of water). Cleaning may be performed with an auto scrubber and approved pad (3M's Blue Cleaner Pad 5300).
- 2. Pick up soiled solution with a wet/dry vacuum.
- 3. Rinse with clean water misted onto floor and remove with wet vacuum or floor extractor.
- 4. Allow floor to dry thoroughly before use (6 8 hrs).