



## Maintenance | Earthflex

### STEPS

#### Initial Maintenance

<b>Cleaning Products</b>	Diversy Profi
<b>Dilute oz/gal</b>	10oz
<b>Equipment</b>	Micro-fiber mop or 3M Red Buffer Pad 5100

#### Regular Maintenance

<b>Cleaning Products</b>	Diversy Profi
<b>Dilute oz/gal</b>	2-4oz
<b>Equipment</b>	Micro-fiber mop or 3M Red Buffer Pad 5100

#### Heavy Soil & Restorative Cleaning

<b>Cleaning Products</b>	Diversy Profi
<b>Dilute oz/gal</b>	16oz
<b>Equipment</b>	Micro-fiber mop or 3M Red Buffer Pad 5300

#### INITIAL MAINTENANCE

1. Remove all surface dirt and debris by vacuuming, sweeping, damp cloth or microfiber mop (Rubbermaid Reveal Spray Mop). Commercial grade electric auto scrubber/extractor equipment is recommended for large or high-traffic areas. Use the softest bristle attachment or red buffer pads available with minimum pressure.
2. Scrub the area using approved cleaning solution (10oz/gal of water), low speed buffer, buffer pad or micor-fiber mop. Avoid flooding the flooring. This is very important as flooding or excess water can lead to moisture between seams which may result in splitting seams. A mist spray should be used to project cleaning solution.
3. Pick up solution with a wet vacuum.
4. Rinse with clean water and remove with a wet vacuum or floor extractor.
5. Repeat rinsing until water removed is clean.
6. Allow to dry before use (6-8hrs).

#### REGULAR MAINTENANCE

1. Remove all surface dirt and debris by vacuuming, sweeping, damp cloth or microfiber mop (Rubbermaid Reveal Spray Mop). Commercial grade electric auto scrubber/extractor equipment is recommended for large or high-traffic areas. If using a commercial floor cleaner, use the softest bristle attachment or red buffer pads available with minimum pressure. PLAE recommends the use of a 3M 7200 Black Stripper pad and low speed buffer.
2. Scrub the area using Diversy Profi (2-4oz/gal of water), micro-fiber mop (or buffer pad). Avoid flooding the flooring. This is very important as flooding or excess water can lead to moisture between seams which may result in splitting seams. A mist spray should be used to project cleaning solution.

#### HEAVY SOIL & RESTORATIVE CLEANING

1. Heavy scrub the area using approved cleaning solution (16oz/gal of water). This cleaning may be performed with an auto scrubber and approved pad (3M Blue Cleaner Pad 5300).
2. Vacuum soiled solution with a wet/dry vacuum.
3. Rinse with clean water.
4. Allow floor to dry thoroughly (6-8hrs).

PLAE warrants against manufacturing defects in Earthflex for a period of five (5) years from the date of manufacturing. Warranty does not cover damage to installed materials due to improper installation, misuse, abnormal wear and tear or methods of upkeep. Warranty is in lieu of any other warranty, whether expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose.

This warranty does not cover floor damage caused (in whole or in part) by fire, winds, floods, moisture, other unfavorable atmospheric conditions or chemical action, nor does it apply to damage caused by ordinary wear, misuse, abuse, negligent or intentional misconduct, aging, faulty building construction, concrete slab separation, faulty or unsuitable subsurface or site preparation, settlement of the building walls or faulty or unprofessional installation. PLAE shall not be liable for incidental or consequential losses, damages or expenses directly or indirectly arising from the sale, handling, or use of the materials (goods) or from any other cause relating thereto.